# Product data sheet

Specifications




## 30mm Push Buttons, package containing 9001KR1UH13 momentary push button operator, START and STOP legend plates

9001AB1

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | Harmony 9001K |
| **Product or Component Type** | Push-button |
| **Device short name** | K |
| **Type of operator** | spring return |
| **Operator profile** | White full guard<br>Orange full guard<br>Black full guard<br>Red full guard<br>Green full guard<br>Yellow full guard<br>Blue full guard |
| **Operator additional information** | With 2 legends START and STOP |

## Complementary

| | |
|---|---|
| **Bezel material** | Chromium plated metal |
| **Mounting diameter** | 1.2 in (30 mm) |
| **Contacts type and composition** | 1 C/O |
| **[Ie] rated operational current** | 10 A, AC-15<br>10 A, DC-15 |
| **Contact operation** | Standard |
| **Device presentation** | Complete product |
| **Cap/operator or lens colour** | 7 colours choice |

## Environment

| | |
|---|---|
| **Product Certifications** | CSA LR 25490 class 3211 03<br>UL listed file E42259 CCN NKCR<br>CE<br>NEMA |
| **IP Degree of Protection** | IP65/IP66 |
| **NEMA degree of protection** | NEMA 3R/6/13 |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US1IPOP22750 |
| **Discount Schedule** | IPOP |
| **GTIN** | 785901849179 |
| **Returnability** | No |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 5.100 in (12.954 cm) |
| **Package 1 Width** | 5.100 in (12.954 cm) |
| **Package 1 Length** | 2.000 in (5.080 cm) |
| **Package weight(Lbs)** | 6.240 oz (176.901 g) |
| **Unit Type of Package 2** | CAR |
| **Number of Units in Package 2** | 20 |
| **Package 2 Height** | 13.000 in (33.020 cm) |
| **Package 2 Width** | 13.000 in (33.020 cm) |
| **Package 2 Length** | 16.500 in (41.910 cm) |
| **Package 2 Weight** | 9.879 lb(US) (4.481 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Use Better

#### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **Yes** |
| Packaging without single use plastic | **No** |
| SCIP Number | **Ae0c4eb9-0bfb-40a4-851f-5c619fbe777d** |
| EU RoHS Directive | **Compliant By Exemption** |
| REACh Regulation | **Reference contains Substances of Very High Concern above the threshold** |
| California proposition 65 | **WARNING: This product can expose you to chemicals including: Lead and Nickel (Metallic), which are known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.** |

### Use Again

#### Repack and remanufacture

| | |
|---|---|
| Take-back | **No** |

Image of product in real life situation

